



Patents Held

Features

Green Power



- Standard/Din Rail Mounting Dual Purpose
- No-load Consumption is lower than 0.3W (No Display)
- Comply with High Efficiency Power 80Plus Criterion
- Comply with 2010. Energy Conservation Power Erp Regulation
- " Output Voltage Monitor " Display
- Convection cooled high reliability
- Wide input range
- 100% burn-in test
- 1 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS: 102(H) \* 75.5(D) \* 45(W)mm

WEIGHT: 181g

General specification

INPUT

Input range 90~264VAC  
127~380VDC  
Input frequency 47~63Hz  
Inrush current (25°C) 20A/110VAC  
40A/220VAC

OUTPUT

Hold-up time 13ms  
Short protection Autorecovery  
Over load protection Automatic power limited

Detail specification

40~50 Watts 12Vdc & 24Vdc Model stocked in UK - 5Vdc model available on request

MODEL	O/P Volt Adj. ± %	Load(Current) <sup>1</sup>			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
LP1040D-05S	V : +5V ±10%	0A	8.0A	8.0A	50mV	±1%	±1%	81% Ref.	7.13 ~ 7.88V
LP1050D-12S	V : +12V ±10%	0A	4.2A	4.2A	120mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V
LP1050D-24S	V : +24V ±10%	0A	2.1A	2.1A	240mV	±1%	±1%	86% Ref.	31.4 ~ 34.7V

Please choose functions and fill in The blanks

Order Model: LP1050D-12S

Optional Function:

Terminal Block: " " : PCB Barrier Terminal Block ← "E" : Mini Terminal Block ←  
 Motion: " " : No Monitor ← "D" : Monitor Display ←  
 Type: " " : No Display Function ← "A" : Output Voltage Display ←

EMC Standards

EN 55022 CLASS A  
 EN 61000-3-3,  
 EN 55024 (IEC 61000-4-2,  
 IEC 61000-4-3, IEC 61000-4-4,  
 IEC 61000-4-5 IEC 61000-4-6,  
 IEC 61000-4-8 IEC 61000-4-11)

Safety Standards

UL 508 APPROVAL  
 CE Marking

Environment

Operating Temperature -15 ~ 50°C, Ambient  
 Operating Humidity 5 ~ 95% RH, No Condensing  
 Storage Temperature -20 ~ 85°C, Ambient  
 Vibration 2G, 10~500Hz, 3 axes

NOTE

1. Each output can provide up to maximum load, but total load cannot exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & noise are measured at 20MHz of bandwidth by using a 20cm long 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output voltage monitor display models. no-load power consumption of 1.5W. and no Energy Conservation Power Erp Regulation.
8. Reign Power reserve the right to change specifications at any time without notice.

WEB : <http://www.switching-powers.com>  
 E-mail : [reignpower@switching-powers.com](mailto:reignpower@switching-powers.com)

Tel : 886-2-22997550  
 Fax : 886-2-22997596

